

RSMS (VSAM)

RSMS Typ/Kabelab- setzmaß	Einzelverbinder				Aderverbindungsleisten	
	Leiterdurch- messer [mm]	Einzelader- verbinder/ Knopfverbinder [DA*]	Durchgangs- verbinder [DA*]	AVH Adernver- bindungs- hülsen [DA*]	AVL 10/20DA [DA*]	AVL 25DA [DA*]
43/8-130 (VASM1/6)	0.4	10-30	10-30	10-30	-	-
	0.5-0.6	10-30	10-30	10-30	-	-
	0.8-0.9	10	10	10	-	-
43/8-180 (VASM 1/6L)	0.4	10-30	10-30	10-30	-	-
	0.5-0.6	10-30	10-30	10-30	-	-
	0.8-0.9	10	10	10	-	-
43/8-240	0.4	10-50	-	10-50	-	-
	0.5-0.6	10-30	-	10-30	-	-
	0.8-0.9	10-20	-	10-20	-	-
43/8-340	0.4	10-75	10-75	10-75	50-100	50-100
	0.5-0.6	10-50	10-50	10-50	50-75	50-75
	0.8-0.9	10-30	10-30	10-30	10-50	10-50
72/15-160 (VASM 2/6)	0.4	50-75	50-75	50-75	150	150
	0.5-0.6	50-75	50-75	50-75	100	100
	0.8-0.9	10-50	10-50	10-50	50	50
72/15-210 (VASM 2/6L)	0.4	50-100	50-100	50-100	50-150	50-150
	0.5-0.6	50-75	50-75	50-75	50-100	50-100
	0.8-0.9	10-50	10-50	10-50	10-100	10-100
72/15-340	0.4	50-100	50-100	50-100	50-150	50-150
	0.5-0.6	50-75	50-75	50-75	50-100	50-100
	0.8-0.9	10-75	10-75	10-75	10-100	10-100
72/15-460	0.4	50-150	50-150	50-150	50-300	50-300
	0.5-0.6	50-100	50-100	50-100	50-200	50-200
	0.8-0.9	10-75	10-75	10-75	10-100	10-100
93/25-190 (VASM 3/6)	0.4	-	-	-	400	400
	0.5-0.6	100	100	100	250	250
	0.8-0.9	30-75	30-75	30-75	100	100
93/25-240 (VASM 3/6L)	0.4	200	200	200	200-300	200-300
	0.5-0.6	150	150	150	150-200	150-200
	0.8-0.9	30-100	30-100	30-100	30-150	30-150
93/25-420	0.4	200-300	200-300	200-300	200-500	200-500
	0.5-0.6	150-200	150-200	150-200	150-300	150-300
	0.8-0.9	30-150	30-150	30-150	30-200	30-200
122/28-190 (VASM 4/6)	0.4	-	-	-	500	500
	0.5-0.6	200	200	200	300	300
	0.8-0.9	75-150	75-150	75-150	-	-
122/28-280 (VASM 5/6)	0.4	250	250	250	250-600	250-600
	0.5-0.6	200-250	200-250	200-250	200-300	200-300
	0.8-0.9	75-200	75-200	75-200	75-300	75-300
122/28-420	0.4	250-600	250-600	250-600	250-900	250-900
	0.5-0.6	200-500	200-500	200-500	200-600	200-600
	0.8-0.9	75-300	75-300	75-300	75-400	75-400
140/34-250	0.4	400	400	400	400-800	400-800
	0.5-0.6	300	300	300	300-500	300-500
	0.8-0.9	10-250	10-250	10-250	100-300	100-300
140/34-330 (VASM 6/6)	0.4	400-600	400-600	400-600	800	800
	0.5-0.6	300-500	300-500	300-500	700	700
	0.8-0.9	100-300	100-300	100-300	400	400

GSMS

GSMS Typ/Kabelabsetzmaß	Einzelverbinder				Aderverbindungsleisten	
	Leiterdurchmesser [mm]	Einzeladerverbinder/ Knopfverbinder [DA*]	Durchgangsverbinder [DA*]	AVH Adernverbindingshülsen [DA*]	AVL 10/20DA [DA*]	AVL 25DA [DA*]
43/8-150	0.4	10-30	10-30	10-30	-	-
	0.5-0.6	10	10-30	10-30	-	-
	0.8-0.9	10	-	10	-	-
43/8-300	0.4	-	10-50	10-50	-	-
	0.5-0.6	10-30	10-50	10-30	-	-
	0.8-0.9	10-30	-	10-20	-	-
55/12-300	0.4	30-75	30-100	30-75	30-100	30-100
	0.5-0.6	20-50	20-100	20-50	20-50	-
	0.8-0.9	10-50	-	10-30	-	-
75/15-250	0.4	50-100	50-150	50-100	50-200	50-250
	0.5-0.6	50-75	50-150	50-75	50-150	50-150
	0.8-0.9	10-50	-	10-50	10-50	10-100
75/15-300	0.4	50-200	50-250	50-150	-	-
	0.5-0.6	50-100	50-250	50-100	-	-
	0.8-0.9	10-100	-	10-75	-	-
75/15-430	0.4	50-250	50-300	50-200	50-300	50-400
	0.5-0.6	50-150	50-300	50-150	50-200	50-250
	0.8-0.9	10-100	-	10-75	10-100	10-150
93/25-250	0.4	200-250	200-300	200	200-300	200-300
	0.5-0.6	150	150-300	150	150-200	150-250
	0.8-0.9	30-150	-	30-100	30-150	30-200
93/25-430	0.4	200-400	200-500	200-400	200-600	200-600
	0.5-0.6	150-300	150-500	150-250	150-400	150-500
	0.8-0.9	30-250	-	30-150	30-250	30-300
93/25-530	0.4	200-400	200-500	200-400	-	-
	0.5-0.6	150-300	150-500	150-250	-	-
	0.8-0.9	30-250	-	30-150	-	-
120/28-250	0.4	250-400	250-500	250-300	250-600	250-600
	0.5-0.6	200-250	200-500	200-250	200-300	200-500
	0.8-0.9	50-250	-	50-200	50-300	50-300
120/28-430	0.4	250-600	250-900	250-500	250-500	250-900
	0.5-0.6	200-400	200-900	200-400	200-600	200-800
	0.8-0.9	50-300	-	50-300	50-400	50-500
120/28-530	0.4	250-600	250-900	250-600	-	-
	0.5-0.6	200-500	200-900	200-500	-	-
	0.8-0.9	50-300	-	50-300	-	-
137/38-430	0.4	400-800	400-900	400-600	400-1000	400-1000
	0.5-0.6	300-600	300-900	300-500	300-600	300-800
	0.8-0.9	100-300	-	100-300	100-400	100-500
137/38-530	0.4	400-800	400-900	400-600	400-1000	400-1000
	0.5-0.6	300-600	300-900	300-500	300-600	300-800
	0.8-0.9	100-300	-	100-300	100-400	100-500

GSMK

GSMK Typ/Kabelab- setzmaß	Einzelverbinder				Aderverbindungsleisten	
	Leiterdurch- messer [mm]	Einzelader- verbinder/ Knopfverbinder [DA*]	Durchgangs- verbinder [DA*]	AVH Adernver- bindungs- hülsen [DA*]	AVL 10/20DA [DA*]	AVL 25DA [DA*]
43/8-200	0.4	10-30	10-50	10-50	-	-
	0.5-0.6	10-30	10-30	10-30	-	-
	0.8-0.9	10-20	-	10-20	-	-
43/8-250	0.4	10-50	10-75	10-75	-	-
	0.5-0.6	10-30	10-75	10-30	-	-
	0.8-0.9	10-30	-	10-30	-	-
75/15-300	0.4	100	150	50-100	75-200	30-100
	0.5-0.6	75	75-150	50-75	50-100	-
	0.8-0.9	10-50	-	10-50	30-100	-
75/15-350	0.4	75-200	75-250	75-150	-	50-250
	0.5-0.6	50-150	50-250	50-100	-	50-150
	0.8-0.9	30-100	-	30-75	-	10-100
75/15-500	0.4	75-250	75-300	75-200	75-300	-
	0.5-0.6	50-150	50-300	50-150	50-200	-
	0.8-0.9	30-100	-	30-100	30-100	-
93/25-300	0.4	200-250	200-300	200	200-300	50-400
	0.5-0.6	150-200	150-300	150	150-200	50-250
	0.8-0.9	50-150	-	50-100	50-150	10-150
93/25-500	0.4	200-400	200-500	200-400	200-600	200-300
	0.5-0.6	150-300	150-500	150-250	150-400	150-250
	0.8-0.9	50-250	-	50-150	50-250	30-200
93/25-600	0.4	200-400	200-500	200-400	-	200-600
	0.5-0.6	150-300	150-500	150-250	-	150-500
	0.8-0.9	50-250	-	50-150	-	30-300
120/28-400	0.4	300-500	300-600	300-400	300-600	-
	0.5-0.6	200-400	200-600	200-300	200-300	-
	0.8-0.9	50-250	-	50-250	50-300	-
120/28-500	0.4	300-600	300-900	300-500	300-900	250-600
	0.5-0.6	200-400	200-900	200-400	200-600	200-500
	0.8-0.9	50-300	-	50-300	50-400	50-300
120/28-600	0.4	300-800	300-900	300-600	-	250-900
	0.5-0.6	200-500	200-900	200-600	-	200-800
	0.8-0.9	50-300	-	50-300	-	50-500
160/55-500	0.4	800-1000	800-1200	800-900	800-1600	-
	0.5-0.6	400-900	400-1200	400-800	400-1000	-
	0.8-0.9	200-500	-	200-500	200-600	-
160/55-700	0.4	800-1200	800	800-1000	800-1800	400-1000
	0.5-0.6	400-1000	-	400-900	400-1200	300-800
	0.8-0.9	200-600	-	200-600	200-800	100-500
200/65-500	0.4	1200-1800	1200	1200-1800	1200-2400	400-1000
	0.5-0.6	1200	-	800-1200	800-1200	300-800
	0.8-0.9	250-800	-	250-800	250-800	100-500
200/65-700	0.4	1200-2400	1200	1200-2400	-	-
	0.5-0.6	1200	-	-	-	-
	0.8-0.9	250-800	-	-	-	-

GSMK-P

GSMK-P Typ/Kabelab- setzmaß	Einzelverbinder				Aderverbindungsleisten	
	Leiterdurch- messer [mm]	Einzelader- verbinder/ Knopfverbinder [DA*]	Durchgangs- verbinder [DA*]	AVH Adernver- bindungs- hülsen [DA*]	AVL 10/20DA [DA*]	AVL 25DA [DA*]
62/15-300	0.4	100	150	50-100	-	-
	0.5-0.6	75	75-150	50-75	-	-
	0.8-0.9	10-50	-	10-50	-	-
62/15-350	0.4	75-200	75-250	75-150	-	-
	0.5-0.6	50-150	50-250	50-100	-	-
	0.8-0.9	30-100	-	30-75	-	-
62/15-500	0.4	75-250	75-300	75-200	75-200	30-100
	0.5-0.6	50-150	50-300	50-150	50-100	-
	0.8-0.9	30-100	-	30-100	30-100	-
93/30-300	0.4	200-250	200-300	200	-	50-250
	0.5-0.6	150-200	150-300	150	-	50-150
	0.8-0.9	50-150	-	50-100	-	10-100
93/30-500	0.4	200-400	200-500	200-400	75-300	-
	0.5-0.6	150-300	150-500	150-250	50-200	-
	0.8-0.9	50-250	-	50-150	30-100	-
93/30-600	0.4	200-400	200-500	200-400	200-300	50-400
	0.5-0.6	150-300	150-500	150-250	150-200	50-250
	0.8-0.9	50-250	-	50-100	50-150	10-150
120/35-400	0.4	300-500	300-600	300-400	200-600	200-300
	0.5-0.6	200-400	200-600	200-300	150-400	150-250
	0.8-0.9	50-250	-	50-250	50-250	30-200
120/35-500	0.4	300-600	300-900	300-500	-	200-600
	0.5-0.6	200-400	200-900	200-400	-	150-500
	0.8-0.9	50-300	-	50-300	-	30-300
120/35-600	0.4	300-800	300-900	300-600	300-600	-
	0.5-0.6	200-500	200-900	200-600	200-300	-
	0.8-0.9	50-300	-	50-300	50-300	-
160/55-500	0.4	800-1000	800-1200	800-900	300-900	250-600
	0.5-0.6	400-900	400-1200	400-800	200-600	200-500
	0.8-0.9	200-500	-	200-500	50-400	50-300
160/55-700	0.4	800-1200	800-	800-1000	-	250-900
	0.5-0.6	400-1000	-	400-900	-	200-800
	0.8-0.9	200-600	-	200-600	-	50-500
200/65-500	0.4	1200-1800	1200-	1200-1800	800-1600	-
	0.5-0.6	1200	-	800-1200	400-1000	-
	0.8-0.9	250-800	-	250-800	200-600	-
200/65-700	0.4	120-2400	1200-	1200-2400	800-1800	400-1000
	0.5-0.6	1200	-	-	400-1200	300-800
	0.8-0.9	250-800	-	-	200-800	100-500